



Size	Ød	L	H1	H2	H3	□A	비고
15A	15	132	27	28	43	50	
20A	20	144	32	32	52	56	
25A	25	160	36	42	65	62	
32A	32	186	45	51	78	78	
40A	40	206	53	60	93	92	
50A	50	231	67	71	116	112	

No	Name of Parts	Material	Remarks
8	Drain Plug	STS304	
7	Hex Bolt	STS304	
6	O-Ring	NBR	
5	Sight Glass	R.Glass	
4	Gasket	C3700	
3	Screen	STS304	
2	Cover	A351CF8	SCS13
1	Body	A351CF8	SCS13

**BILL OF MATERIAL**

**FOR INFORMATION**

**SPECIFICATIONS**

Applicable Fluid	Water, Oil & Gas	
Working Pressure	0.35 ~ 10kg/cm <sup>2</sup> G	
Applicable Temperature	Max. 80°C	
Connection (Optional)	KS 10K RF Flanged	
Screen Data	Standard	Ø1.5mm
	Optional	Wire Net(메쉬스크린)

\* Wire net ; 20,30,40,60,80,100,150,200Mesh

ITEM	OMEGA STRAINER (FLANGE TYPE)		
MODEL	OMS-10F	DWG No	OMS-10F-023
SIZE	15-50A	DATE	2024.1.23

**OMEGA VALVE**

Better savings  
Better efficiency